

# GSM FIXED CELLULAR TERMINAL

## FCT-335



- GSM 850/900/1800/1900MHz
- GSM WLL residential applications
- Cutting cost of calls from landline phones to mobiles
- Connecting metering box for payphone use

### Environment

- Operating temperature range : -10 to +45 degree C
- Storage temperature range : -25 to +65 degree C
- Humidity : 45% to 95%
- Dimensions : 220mm(W)x140mm(H)x35mm(D)
- Weight : Appx. 0.8Kgs

## MAXCOMM CO., LTD.

WWW.MAXCOMM.COM.TW

al.rock@msa.hinet.net, info@maxcomm.com.tw

Tel: 886 2 2966 6648 Fax: 886 2 2969 8296

4F, 283, COUNTY BLVD. SEC.1, BAN CHIAO 220,  
TAIPEI HSIEN, TAIWAN R.O.C

### Main Features

- User-friendly installation; Plug & Play
- 2-phone connection
- LED indicators for signal strength, status and power
- SIM Card locking and Network locking
- Reverse Polarity signal support
- DTMF and pulse dialing
- Emergency Battery back-up
- SMS(optional)
- USB Connector for PC connection(optional)
- GPRS Data transmission(optional)

### Technical Specification

- **Air Interface :**  
GSM Phase I/GSM Phase II + compatible
- **GSM Frequency :** GSM 850/900/1800/1900 MHz
- **RF Transmit Power :** 2W (900 MHz), 1W (1800 MHz)
- **RF Sensitivity :** < -100 dBm
- **Electricity Power Supply :**  
Input: AC100~240V/60Hz ; Output: DC12V/600mA
- **Optional 6-pcs Ni-Mh re-charged Batteries**
- **LED Indicators :**  
Power / Signal strength / Network status
- **Connectors :**  
RJ-11 Interface jack for telephone  
USB interface jack for PC(optional)  
SMA antenna connector  
DC power input jack
- **Antenna :**  
2dbi Omni Antenna  
High-gain antenna and cable as optional

**Specifications are subject to change without notice**