

GSM FIXED WIRELESS PHONE

MW10

- GSM 850/900/1800/1900MHz
- GSM WLL residential applications
- Cutting cost of calls from landline phone to mobile



Main Features

- GSM Quad-Band selectable
- USB Data port
- 11 function keys for menu navigation
- SIM Card locking, Network locking, Base Station locking
- User-friendly Operation with mobile phone like menu
- 128x64dots backlit graphic LCD Display
- SMS and call log function
- Signal strength and battery capacity indication on display
- Rechargeable Ni-MH battery as back up power
- Speaker phone for handfree feature

Environment

- **Operating temperature range** : 0 to +55 degree C
- **Storage temperature range** : -10 to +65 degree C
- **Humidity** : 5% to 95%
- **Dimensions** : 215mm(L)x178mm(W)x75mm(H)
- **Weight** : Appx. 1Kgs

MAXCOMM CO., LTD.

WWW.MAXCOMM.COM.TW

al.rock@msa.hinet.net, info@maxcomm.com.tw

Tel: +886 2 2966 6648 Fax: +886 2 2969 8296

4F, 283, COUNTY BLVD. SEC.1, BAN CHIAO,

TAIPEI HSIEN 220, TAIWAN

Technical Specification

Air Interface :

GSM Phase I / GSM Phase II + compatible

GSM Frequency Ranges :

GSM 900/1800 or GSM 850/1900MHz selectable

- Rx Frequency 935~960MHz
- Tx Frequency 890~915MHz

- Rx Frequency 1805~1880MHz
- Tx Frequency 1710~1785MHz

RF Transmit Power :

2W (900 MHz), 1W (1800 MHz)

RF Sensitivity : < -104 dBm

Electricity Power Supply :

- Input: AC220V/60Hz
- Output : 7.5V, 1.6A

Battery Supply :

- Rechargeable Ni-MH Battery x3
- Capacity: 1300mAh x3

Antenna : fixed antenna

- External Omni or Yagi Antenna with cable as an option

Specifications are subject to change without notice