

GSM FIXED WIRELESS PHONE

MW13



- GSM 850/900/1800/1900MHz
- GSM WLL residential applications
- Cutting cost of calls from landline phone to mobile

Main Features

- GSM Four-Band compatible
- English/Spanish language display selectable
- 32mb flash memory
- STK & AMR features support
- SIM Card locking, Network locking, Base Station locking
- User-friendly Operation with mobile phone like menu
- Large backlit graphic LCD Display
- SMS and call log function
- Signal strength and battery capacity indication on display
- Rechargeable Ni-MH battery as back-up power
- Handfree speaker phone for feature

Environment

- **Operating temperature range** : 0 to +55 degree C
- **Storage temperature range** : -10 to +65 degree C
- **Humidity** : 5% to 95%
- **Dimensions** : 200mm(L)x170mm(W)x55mm(H)
- **Weight** : Appx. 1Kgs

MAXCOMM CO., LTD.

WWW.MAXCOMM.COM.TW

info@maxcomm.com.tw; al.rock@msa.hinet.net

Tel: +886 2 2966 6648 Fax: +886 2 2969 8296

4F, 283, COUNTY BLVD. SEC.1, BAN CHIAO,
TAIPEI HSIEN 220, TAIWAN

Technical Specification

Air Interface :

GSM Phase I / GSM Phase II + compatible

GSM Frequency Ranges :

GSM 850/900/1800/1900MHz auto-selective or manual

- Rx Frequency 935~960MHz
- Tx Frequency 890~915MHz

- Rx Frequency 1805~1880MHz
- Tx Frequency 1710~1785MHz

RF Transmit Power :

2W (900 MHz), 1W (1800 MHz)

RF Sensitivity : <-103 dBm

Electricity Power Supply :

- Input: AC220V/60Hz
- Output : 4.6V, 1000mA

Battery Supply :

- Rechargeable Ni-MH Battery x3
- Capacity: 1300mAh x3 (higher capacity as optional)

Antenna : fixed antenna 2.5dbi

- External Omni or Yagi Antenna with cable as an option

Specifications are subject to change without notice