

3G Fixed Wireless Phone MW-32



3G Fixed Wireless Phone MW-32

Description:

MaxComm 3G Fixed Wireless Phone MW-32 is designed to meet 3G operator and the public's requirements by providing competitive tariff as well as public communication in rural area and downtown business district. Moreover, its easy & quick installation without laying any copper lines makes it perfect alternative to the PSTN phones. Integrated design for inside self-charging circuit of backup battery power, external antenna with high gain, perfects its mobility and portability. It also provide high speed wireless connectivity for internet access by using 3G network. It is indeed the opportunity to once again render the phone industry a profitable business.

Add: 4Fl, No.283, County-Boulevard Sec.1, Ban-Chiao 220, Taipei Hsien, Taiwan

Tel: 886-2-2966-6648

Email: info@maxcomm.com.tw

Fax: 886-2-2969-8296

Web: WWW.MAXCOMM.COM.TW

VOICE Features:

- ◆ WCDMA module embedded .
- ◆ Large LCD display
- ◆ CLIP (Call Line Identification Presentation)
- ◆ Voice mail and Short Message Service
- ◆ Call hold, call waiting, call forward, call transfer, call barring
- ◆ Three party conferencing
- ◆ Speed dialing
- ◆ SIM lock, network lock, cell lock
- ◆ Emergency call without SIM card
- ◆ High gain antenna
- ◆ Powerful phone book
- ◆ Backup poly-li battery
- ◆ Incoming call reminder
- ◆ Hands Free Available
- ◆ Call Records
- ◆ USB interface for high speed data transfer

DATA Features:

- ◆ USB interface for data
- ◆ Multimode operation –HSUPA/HSDPA/UMTS/EDGE/GPRS/GSM
- ◆ Triple-band HSPA/UMTS 850/1900/2100 MHz
- ◆ Quad-band EDGE/GPRS/GSM 850/900/1800/1900 MHz
- ◆ HSDPA downlink up to 3.6 Mbps
- ◆ WCDMA (UMTS) uplink data rate up to 384 kbps
- ◆ EDGE data up to 237 Kbps DL and 118Kbps UL, 3GPP Release4, class 12
- ◆ GPRS data up to 85.6 Kbps DL and 42.8 Kbps UL

Specifications:

◆ Network support

GSM 850/900/1800/1900Mhz

UMTS 850/1900Mhz or 900/2100 MHz

◆ output Power

Class 3 for UMTS/HSDPA/HSUPA

Class 4 for GSM 850/900

Class 1 for GSM 1800/1900

Class E2 for EDGE 900/1800

◆ Dimensions and Weight

Metric (cm) : 20L*17W*6.73H

Weigh : 0.43kg

◆ Environment

Operating temperature range: -10°C to +50°C

Humidity: 5% to 95% (non-condensing)

◆ 128*64 pix LCD Display

◆ Backup battery: Poly-lithium battery $\geq 3.7\text{v}/850\text{mAh}$

Stand by hours: up to 36 Hours (Network depended)

Talk time: up to 5 Hours (Network depended)