

CDMA 800/450MHz EVDO Rev.A WiFi Router WR-35E



Technical Specification

- **Air Interface :**
EVDO/CDMA2000 1x 450/800/1900MHz
- **EVDO Rev. A:** 3.1Mbps downlink/1.8Mbps uplink
- **AC/DC Power Supply :**
Input: AC100~240V/50~60Hz, 0.68A
Output: DC 9V/1.5A
Car Power Charger: 5V
- **Connectors :**
2 RJ-45(LAN) port or 1 LAN+1 WAN(optional)
1 DC power input jack
- **Antenna :** Internal WiFi/EVDO/CDMA high gain antenna;
optional external antenna for EVDO/CDMA available
- **Indicators :** Power,Connect,WiFi,Signal,Network Mode
- **WiFi :** IEEE 802.11b/g/n protocol
- **WPS:** WiFi Protected Setup supportd



Main Features

- Built-in EVDO Rev. A modem at a rate of 3.1Mbps downlink / 1.8Mbps uplink
- Optional VPN & VLAN function support
- LED indicators: Power,Diag, LAN, WIFI,Roaming, 3G
- Supporting Web base Management and plug & play
- Supporting DHCP Server, NAT, Virtual Server, SNTP, Static Routing, DNS Relay, UPnP, DMZ, MAC/URL/ IP filter, VPN passthrough, WiFi 802.11b/g/n
- Optional external 3G antenna
- RJ-45 LAN ports for 2 users to log on 3G network (not including WiFi users)
- 3G fail-over backup by WAN ADSL

Environment

- **Operating temperature :** 0°C to 50°C
- **Operation Humidity :** 10% to 90%
- **Dimensions :** 160mm(L)x115mm(W)x35mm(H)
- **Weight :** <500 g

4F, NO. 283, COUNTY BLVD., SEC. 1, BAN CHIAO,
TAIPEI HSIEN 220, TAIWAN, R.O.C.

WWW.MAXCOMM.COM.TW

TEL: 886 2 2966 6648

FAX: 886 2 2969 8296

E-mail: INFO@MAXCOMM.COM.TW